



3-211 Compression Rod Latch RS / FS



Advantages

- Rod latch for installation inside door sealing, with compression 4mm.
- Single or multi-point latching by using of additional latching devices.
- The connecting rods between the latching devices can be fixed easily in guides.
- Seismic-proof according to GR-63-CORE, Issue 4.
- Vibration-proof according to DIN EN 61373.
- For round rods Ø8mm or flat rods 3 x 14 mm.
- Oblong hole allows for installation adjustment.
- RH and LH version.
- Grounding by grounding clip.

Materials

- **Housing, driving rods, clamps, pinion:** zinc die

Remarks

- Closing process:
1. A 90° turn of the swinghandle brings the cam into the locked position.
 2. With another 45° turn the cam is pressed by 4mm against the clamping surface.



Rod Latch with compression, 2 driving rods

	Part Number	Version	Stroke	Installation type
a)	208-9076.00-00000	LH	23 mm	screw-on
a)	208-9077.00-00000	RH	23 mm	screw-on

Rod Latch with compression, 1 driving rod

	Part Number	Version	Stroke	Installation type
b)	208-9078.00-00000	LH	23 mm	screw-on
c)	208-9079.00-00000	RH	23 mm	screw-on



Accessories

1-102.01 **Cams L45 Steel**

d) 3-220 **Rod Latch Adapter for Compression Rod Latch**

3-215 **90° Redirect for Multi-Point Locking System**

3-221 **Rods for Compression Rod Latch**

3-203 **Swinghandle for Compression Rod Latch**

3-011 **Grounding Clip Stainless Steel**



